

Key Features

Soft Start/Stop operation
Auto safety function
Auto force sensing
Two 3 channel mini-remotes
Rolling code technology
Up to 64 memory registers
Courtesy light (LED)
Manual release handle
Minimal side room 95mm
2 year motor warranty

Accessories

Safety beam sensors
Motion detecting control panel
Keyed manual release
Single channel remote
2 or 4 channel mini-remote
Wireless wall button
Wireless keypad
Optional Evercharge™ Standby Power Unit

Specifications

24 DC motor with thermal overload protection
Input voltage: 240V AC
Rated door area 12.5m²
Rated door weight: 80kg
Pulling force: 500N
433.92 MHz AM radio with rolling code

Standard slimline roller door opener for single or standard double door garages



Rated door area	Rated door weight	Pulling force	Motor
12.5m ²	80kg	500N	DC

Easy installation even in tight side clearance situations for doors up to 12.5m²

Soft Start/Stop:

The MR600 is equipped with Chamberlain Soft Start/Stop technology. This is designed to ensure smooth and quiet door operation

Automatic Safety Function:

With its automatic safety function your garage door will stop and reverse automatically if obstructed going down or stop if obstructed going up. Your door can also be stopped and locked at any height for ventilation

Automatic Force Sensing:

Equipped with automatic force sensing, with each operation the garage door opener monitors and adjusts the force needed to open your garage door

Three Channel Mini-Remote:

A three channel mini remote control with rolling code technology can control up to three different doors or gates

Manual Release:

In case of power failure you can simply activate the manual release to open your garage door

Accessories:

A wide range of accessories is available for this motor. Refer to our website (www.chamberlainanz.com) for further details

Warranty:

The MR600 comes with a two year general warranty