Merlin Professional MR800

Powerful slimline roller door opener for single and heavy double door garages





Rated door area	Rated door weight	Pulling force	Motor
16.5m²	100kg	550N	DC

Easy installation even in tight side clearance situations for doors up to 16.5 m^2 *

Soft Start/Stop:

The MR800 is equipped with Chamberlain Soft Start/Stop technology. This is designed to ensure smooth and quiet door operation

Automatic Safety Function:

With its automatic safety function your garage door will stop and reverse automatically if obstructed going down or stop if obstructed going up. Your door can also be stopped and locked at any height for ventilation

Automatic Force Sensing:

Equipped with automatic force sensing, with each operation the garage door opener monitors and adjusts the force needed to open your garage door

Three Channel Mini-Remote:

A three channel mini remote control with rolling code technology can control up to three different doors or gates

Wireless Wall Button:

Wireless push button equipped with rolling code technology for remote operation in the garage or home

Manual Release:

In case of power failure you can simply activate the manual release to open your garage door

Accessories:

A wide range of accessories is available for this motor. See page 12 for details

Warranty:

The MR800 comes with a two year general warranty and a five year warranty on the motor

Key Features

Soft Start/Stop operation

Auto safety function
Auto force sensing
Two 3 channel miniremotes
Wireless wall button
Rolling code technology
Up to 64 memory
registers
Manual release handle

Courtesy light (LED)
Minimal side room 95mm
5 year motor warranty

Accessories

Safety beam sensors
Motion detecting
control panel
Keyed manual release
Single channel
remote

2 or 4 channel miniremote Wireless keypad Optional Evercharge™

Standby Power Unit

Specifications

24V DC motor with thermal overload protection

Input voltage: 240V AC Rated door area: 16.5m^{2*} Rated door weight: 100kg Pulling force: 550N 433.92 MHz AM radio with rolling code

* Only with safety beam sensors